

Mobile E-Cell* Trailer

Description and Use



Mobile E-Cell trailers from GE provide emergency, interval, or long-term service for de-ionized water needs. The E-cell trailer produces high purity water using electro-deionization (EDI) technology. Water is de-ionized using electrically regenerated high purity ion exchange resins. No regenerant acids or caustics are required. The Mobile E-Cell trailer contains all the necessary hardware to produce and monitor up to 300 gpm (68 m³/h) of quality water. Monitored parameters include concentrate and permeate conductivity, e-flow, concentrate loop and concentrate recycle flow meters; and feed, product, concentrate loop and pump discharge pressure transmitters. The data gathered is monitored to ensure the Mobile E-Cell trailer is running optimally.

General Properties

Features

- GE Technician operates trailer
- Emergency, Interval and long-term service for E-Cell water needs
- No regenerant acids or caustics required

- Up to 300 gpm (68 m³/h) flow rate
- 16 MOhm.cm (0.06 μmhos) product water
- Able to combine with other GE Mobile Products to enhance system capability

Table1: Trailer Specifications

Dimensions	
Trailer Length	48 ft (14.6 m)
Trailer Height	13 ft, 6 in. (4.1 m)
Trailer Width	8 ft, 6 in. (2.6 m)
Shipping Wt.	@ 40,000 lb (18,143kg)
Operating Wt.	@ 50,000 lb (22,680kg)
System on Board	
Flow Rate	Up to 300 gpm (68 m ³ /h)
Product Water quality	Resistivity 16 MOhm.cm (Cond. 0.06 μmhos)
Nominal Recovery	90 - 95%
Cartridge Filter	5 μ nominal to prevent contamination from external supply
Rectifiers	Redundant Rectifiers
Max. Water Temp.	100°F (38°C)
Min. Water Temp.	45°F (7.2°C)
Nom. Water Temp.	60°-75°F (16°-24°C)
Max. Inlet Pressure	100 psig (6.9 bar)
Min. Inlet Pressure	45 psig (3.1 bar)
HVAC	
The Mobile E-Cell Trailer is climate controlled with an electric HVAC unit.	
Product Water	
Silica	<25 ppb*
Sodium	<2 ppb
Boron	<0.1 ppb
*10 ppb when fed by two-pass RO	
Feed Water (RO Permeate or Equivalent)	
Feed TEA	<25 ppm
Silica	<0.5 ppm
TOC	<0.5 ppm
Hardness	<0.5 ppm



Find a contact near you by
visiting gewater.com or
e-mailing custhelp@ge.com.

Global Headquarters
Trevose, PA
+1-215-355-3300

Americas
Watertown, MA
+1-617-926-2500

Europe/Middle East/Africa
Heverlee, Belgium
+32-16-40-20-00

Asia/Pacific
Shanghai, China
+86-21-5298-4573

Table1: Trailer Specifications (continued)

Connections (Stainless Steel)			
Connection Type	Flange with adapters for Victaulic* and Fire Hoses		
Feed Water Inlet	6-in. (152-mm)		
Outlet (Product)	6-in. (152-mm)		
Clean In Place Inlet	6-in. (152-mm)		
Rinse/Divert Outlet	6-in. (152-mm)		
Clean In Place Outlet	6-in. (152-mm)		
Conc. Bleed	1.5-in. (38.1-mm)		
Electrode Outlet	1-in. (25.4-mm)		
Electrical			
Power re-quirements	One drop of 240 amp 3-phase power (460 VAC)		
Breaker size	250 Amp 3-phase (min.)		
Installed KVA	200 KVA		
Nom. DC Power Consumption	0.2 - 1.5 kWh/1000 gal (0.05 - 0.4 kWh/m ³)		
Instrumentation			
PLC	GE Fanuc PLC		
Customer tie-in	Analog (4-20 mA) and/or discrete tank level for automatic shut down		
Parameters	Feed	Product (Outlet)	Concentrate
(Waste)			
Flow		X	X
Temperature	X		
Resistivity (Conductivity)	X	X	
Pressure	X	X	X
Silica		X	

Safety Precautions

A Material Safety Data Sheet containing detailed information about this product is available on request.